



MODELING THE SIZE EFFECT IN THE MECHANICAL BEHAVIOR OF NANOCOM-POSITES

Dang Phong Bach, Ludovic Cauvin, Delphine Brancherie, Djimedo Kondo

► To cite this version:

Dang Phong Bach, Ludovic Cauvin, Delphine Brancherie, Djimedo Kondo. MODELING THE SIZE EFFECT IN THE MECHANICAL BEHAVIOR OF NANOCOM-POSITES. 6th International Conference on Multi-scale Computational Methods for Solids and Fluids, Jun 2023, Sarajevo, Bosnia and Herzegovina. hal-04404020

HAL Id: hal-04404020

<https://hal.utc.fr/hal-04404020>

Submitted on 18 Jan 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

MODELING THE SIZE EFFECT IN THE MECHANICAL BEHAVIOR OF NANOCOMPOSITES

Dang Phong Bach ¹, Ludovic Cauvin ², Delphine Brancherie ³, Djimédo Kondo ⁴

¹ Université de Technologie de Compiègne, Roberval (Mechanics, energy and electricity),
Centre de recherche Royallieu, CS 60319, 60203 Compiègne Cedex, France

² Université de Technologie de Compiègne, Roberval (Mechanics, energy and electricity),
Centre de recherche Royallieu, CS 60319, 60203 Compiègne Cedex, France, Ludovic.Cauvin@utc.fr

³ Université de Technologie de Compiègne, Roberval (Mechanics, energy and electricity),
Centre de recherche Royallieu, CS 60319, 60203 Compiègne Cedex, France, Delphine.Brancherie@utc.fr

⁴ Sorbonne Université, CNRS, UMR 7190, Institut Jean Le Rond d'Alembert, Paris, France,
Djimedo.Kondo@sorbonne-universite.fr

1. Introduction

With the development of smart materials [1] and the constant search for mass reduction, the use of nanocomposites is constantly growing. Indeed, for very low volume fraction of reinforcements and contrary to classical composites, nanocomposites offer remarkable properties, especially mechanical ones. These remarkable properties can be explained by a size effect induced by the nanometric dimension of the reinforcements. The local phenomena present at the matrix-inclusion interface, which are negligible in the case of classical composites, are no longer so in nano-reinforced materials where the ratio (matrix-inclusion interface surface) / (material volume) becomes much larger. However, taking into account the size effect in the modeling of the behavior of nanocomposites remains a great challenge at the present time. In the context of linear elasticity, many works, taking into account a size effect of nano-fillers, have been carried out by means of analytical approaches [2, 3, 4] using micromechanical models. Compared to classical micromechanical model like the Mori-Tanaka scheme or the Hashin-shtrikman bounds, a coherent interface is introduced on the matrix-inclusion interface and the equilibrium of this interface is taken into account. The behavior of this interface is generally governed by an elastic law as presented by Bottomley et al [5]:

$$\sigma_s = \mathbb{C}^s : \varepsilon_s \quad (1)$$

where \mathbb{C}^s is the surface stiffness tensor of the interface, σ_s is the surface tangent stress on the interface and ε_s is the surface strain tensor on the interface given by :

$$\varepsilon_s = \mathbf{P} \cdot \varepsilon \cdot \mathbf{P} \quad (2)$$

\mathbf{P} is the second order projection operator on the interface :

$$\mathbf{P} = \mathbf{I} - \mathbf{n} \otimes \mathbf{n} \quad (3)$$

In addition to the classical bulk equilibrium, these analytical approaches take account the equilibrium of the interface through the generalized Young-Laplace equation on the matrix-inclusion interface [6, 7, 8]:

$$\text{div}_s \sigma_s + \llbracket \sigma \rrbracket \cdot \mathbf{n} = \mathbf{0} \quad \forall \mathbf{x} \in \Gamma ; \Gamma \text{ being the matrix-inclusion interface.} \quad (4)$$

Because of analytical difficulties, micromechanical models accounting for the size effect of the nano-inclusions are limited to spherical or cylindrical inclusions. To overcome this limitations, numerical

strategies have been developed [9, 10, 11, 12]. In this communication, we will present the finite element models we propose in the context of both elastic and non-linear behaviors.

2. Problem definition




Figure 1: Two-phase material with imperfect matrix-inclusion interface.

Here we consider a bounded domain $\Omega \subset \mathbb{R}^d$ ($d = 2$ or 3) with boundary $\partial\Omega$ ($\partial\Omega = \partial\Omega_F \cup \partial\Omega_u$ and $\partial\Omega_F \cap \partial\Omega_u = \emptyset$). $\tilde{\mathbf{n}}$ is the outward unit normal to $\partial\Omega$. The domain Ω is made of two phases $\Omega^{(1)}$ and $\Omega^{(2)}$ corresponding respectively to the inclusion and the matrix. These 2 domains are separated by an imperfect interface Γ (Fig.1). We note \mathbf{n} the unit normal vector to Γ , chosen from $\Omega^{(1)}$ to $\Omega^{(2)}$.

As considered in analytical micromechanical model accounting for the size effect of nano-inclusions, the interface is assumed to be coherent, which means that the surface stresses are related to the jump of the traction vector across the interface.

The equilibrium of the 2 phases $\Omega^{(1)}$ and $\Omega^{(2)}$ is given by the equation:

$$\text{div} \boldsymbol{\sigma}^{(l)} + \mathbf{b} = \mathbf{0} \quad \text{in } \Omega^{(l)}, \quad l = 1, 2, \quad (5)$$

where $\boldsymbol{\sigma}$ is the bulk Cauchy stress tensor and \mathbf{b} is a volume force.

The Neumann and Dirichlet boundary conditions are applied on $\partial\Omega$:

$$\boldsymbol{\sigma} \cdot \tilde{\mathbf{n}} = \mathbf{F} \quad \text{sur } \partial\Omega_F \quad \text{et} \quad \mathbf{u} = \bar{\mathbf{u}} \quad \text{sur } \partial\Omega_u, \quad (6)$$

The equilibrium of the coherent interface Γ is governed by the generalized Young-Laplace equation written in eq. (4).

3. Linear and non-linear behavior estimations

Using eq. (5) to eq. (4), assuming Γ closed and without any debonding between matrix and inclusions, the weak form of the problem presented in section 2. can be expressed:

$$\forall \delta \mathbf{u} \quad \int_{\Omega \setminus \Gamma} \nabla^s \delta \mathbf{u} : \boldsymbol{\sigma} d\Omega + \int_{\Gamma} \nabla_s^s \delta \mathbf{u} |_{\Gamma} : \boldsymbol{\sigma}_s d\Gamma - \int_{\Omega \setminus \Gamma} \delta \mathbf{u} \cdot \mathbf{b} d\Omega - \int_{\partial\Omega} \delta \mathbf{u} \cdot \boldsymbol{\sigma} \cdot \tilde{\mathbf{n}} dS = 0. \quad (7)$$

where $\nabla_s^s \{\bullet\} = \nabla^s \{\bullet\} \mathbf{P}$,

$\nabla^s \{\bullet\}$ being the symmetric gradient operator.




Figure 2: Representative Volume Element (in plan $(\mathbf{e}_1, \mathbf{e}_2)$)

On a Representative Volume Element (RVE) (fig. 2) corresponding to the two-phase material problem presented in section 2., using finite element method in plane strain with interface elements, Xfem/level set method or embedded-FEM, the weak form given in eq. (7) will be solved by considering linear and non-linear behaviors in the bulk and elastic behavior on the matrix-inclusion interface. Different diameters of the cylindrical inclusions will be considered to study the impact of their size on both macroscopic and microscopic response of the material. These results and first developments considering several physics will be presented during the conference.

References

- [1] K. Hamdi, Z. Aboura, W. Harizi, K. Khellil. *Improvement of the electrical conductivity of carbon fiber reinforced polymer by incorporation of nanofillers and the resulting thermal and mechanical behavior*, Journal of Composite Materials, 52(11),1495-1503, 2018.
- [2] Duan, H., Wang, J.-x., Huang, Z., Karihaloo, B. L. *Size dependent effective elastic constants of solids containing nano-inhomogeneities with interface stress.*, Journal of the Mechanics and Physics of Solids, 53(7), 1574-1596, 2005.
- [3] Brisard, S., Dormieux, L., Kondo, D. *Hashin-shtrikman bounds on the bulk modulus of a nanocomposite with spherical inclusions and interface effects.*, Computational Materials Science, 48(3), 589-596, 2010.
- [4] Brisard, S., Dormieux, L., Kondo, D. *Hashin-Shtrikman bounds on the shear modulus of a nanocomposite with spherical inclusions and interface effects.*, Computational Materials Science, 50(2), 403-410, 2010.
- [5] Bottomley, DJ, Ogino, T *Alternative to the Shuttleworth formulation of solid surface stress.*, Physical Review B, 63(16), 165412, 2001.
- [6] Povstenko Y.Z. *Theoretical investigation of phenomena caused by heterogeneous surface tension in solids.*, Journal of the Mechanics and Physics of Solids, 41(9), 1499–1514, 1993.
- [7] Gurtin M.E., Weissmüller J., Larche F. *A general theory of curved deformable interfaces in solids at equilibrium*, Philosophical Magazine A, 78(5), 1093–1109, 1998.
- [8] Chen T., Chiu M.S., Weng C.N. *A general theory of curved deformable interfaces in solids at equilibrium*, Journal of Applied Physics, 100(7), 074308, 2006.
- [9] Yvonnet, J., Quang, H. L., He, Q.-C. *An xfem/level set approach to modelling surface/interface effects and to computing the size-dependent effective properties of nanocomposites.*, Computational Mechanics, 42(1), 119-131, 2008.
- [10] Javili, A., Steinmann, P., Mosler, J. *Micro-to-macro transition accounting for general imperfect interfaces.*, Computer Methods in Applied Mechanics and Engineering, 317, 274-317, 2017.
- [11] Bach, D. P., Brancherie, D., Cauvin, L. *Size effect in nanocomposites: Xfem/level set approach and interface element approach.*, Finite Elements in Analysis and Design, 165,41-51, 2019.
- [12] Bach, D. P., Brancherie, D., Cauvin, L. *An embedded-FEM approach accounting for the size effect in nanocomposites.*, Computational Mechanics, 70,745-762, 2022.