

Numerical modeling of thermoelastic nanocomposites

Fahmi Grine, Ludovic Cauvin, Delphine Brancherie, Djimedo Kondo

▶ To cite this version:

Fahmi Grine, Ludovic Cauvin, Delphine Brancherie, Djimedo Kondo. Numerical modeling of thermoelastic nanocomposites. EMI 2023 International Conference, Aug 2023, Palermo, Italy. hal-04404356

HAL Id: hal-04404356 https://hal.utc.fr/hal-04404356

Submitted on 18 Jan2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

EMI 2023 International Conference

Palermo, Italy, August 27 - 30, 2023

Title: Numerical modeling of thermoelastic nanocomposites

Author(s): Fahmi Grine*1, Ludovic Cauvin1, Delphine Brancherie1, Djimédo Kondo2

¹ Université de Technologie de Compiègne, Roberval (Mechanics, energy and electricity), Centre de recherches, CS 60319, 60203 Compiègne Cedex, France, <u>fahmi.grine@utc.fr</u>, <u>ludovic.cauvin@utc.fr</u>, <u>delphine.brancherie@utc.fr</u>

² Sorbonne Universités, Institut Jean Le Rond d'Alembert, UMR 7190 CNRS-SU, F-75005, Paris, France <u>djimedo.kondo@sorbonne-universite.fr</u>

Keyword(s): Nanocomposites, size effect, homogenization, finite element method, thermoelasticity.

Abstract

Nanocomposites have drawn much attention due to their excellent properties for the same reinforcement volume fraction compared to classical composites. Moreover, they can integrate multi-physical properties for multifunctional applications. Such improvement in the material properties is usually explained by the important interface surface/bulk volume ratio in the case of nanocomposites. To study such a class of materials, imperfect interfaces are usually introduced. In the case of thermoelastic materials, such a hypothesis implies discontinuities of the different thermomechanical fields. Nevertheless, the analytical solutions hold only for simple boundary conditions and for spherical or cylindrical inclusions. Therefore, numerical tools are necessary to study nanocomposite materials behavior. Restricted to the linear elasticity and using the generalized Young-Laplace equation for the interface equilibrium, a numerical strategy for nanomaterials modeling is developed in [1] using three numerical methods: interface finite element method, extended finite element methods.

Focusing on thermoelasticity, the formulation derived in [2], based on the introduction of interfacial energy, is considered here. In addition, the hypothesis of continuous displacement and temperature fields holds. Using the interface finite element method, we propose in the present study a numerical tool to deal with coupled time-dependent thermoelastic behavior in the presence of imperfect interfaces. Considering a unidirectional nanofibrous composite, we show that the interface has an important influence on the thermomechanical fields and then on the effective response of the REV. Besides, a numerical homogenization scheme is used with different boundary conditions as illustrated in [3]. Taking advantage of the proposed numerical tool, the effect of the reinforcement size on the effective thermoelastic parameters is studied for different fibers shapes. It is noteworthy that even if the interface behavior is restricted to linear elasticity, all the thermoelastic parameters are dependent on the fibers cross section radius. Moreover, the qualitative effect of the reinforcement size on the material parameters depends essentially on the different interface moduli.

References

[1] Bach, D. P. "Development of a finite element strategy for the modeling of nano-reinforced materials" (Doctoral dissertation, Université de Technologie de Compiègne), (2020).

[2] Moeckel, G. "Thermodynamics of an interface." Archive for Rational Mechanics and Analysis 57.3, 255-280, (1975).

[3] Quang, H. L., & He, Q. C. "Estimation of the effective thermoelastic moduli of fibrous nanocomposites with cylindrically anisotropic phases" Archive of Applied Mechanics, 79, 225-248, (2009).